

SPAN® IMU-ISA-100C



HIGH PERFORMANCE TACTICAL GRADE IMU COMBINES WITH NOVATEL'S GNSS TECHNOLOGY TO DELIVER 3D POSITION, VELOCITY AND ATTITUDE SOLUTION



SPAN: WORLD-LEADING GNSS+INS TECHNOLOGY

NovAtel's Synchronous Position, Attitude and Navigation (SPAN) technology brings together two different but complementary technologies: Global Navigation Satellite System (GNSS) positioning and inertial navigation. The absolute accuracy of GNSS positioning and the stability of Inertial Measurement Unit (IMU) gyro and accelerometer measurements are tightly coupled to provide an exceptional 3D navigation solution that is stable and continuously available, even through periods when satellite signals are blocked.

OVERVIEW

The IMU-ISA-100C features Northrop-Grumman Litef GMBH's proven inertial measurement technology offering exceptional performance when paired with a NovAtel SPAN receiver. A near navigation grade sensor, the IMU-ISA-100C contains fiber optic gyros and fully temperature compensated Micro Electromechanical Systems (MEMS) accelerometers. The IMU-ISA-100C operates from 10-34 VDC and interfaces with NovAtel's FlexPak6™ or ProPak6™ through a highly reliable IMU interface. IMU measurements are used by the SPAN receiver to compute a blended GNSS+INS position, velocity and attitude solution at rates up to 200 Hz.

ADVANTAGES OF IMU-ISA-100C

The IMU-ISA-100C offers extremely high performance and precise accuracy at an affordable price point. **It is commercially exportable and offers an ideal solution for applications such as platform stabilization, general purpose navigation, photogrammetry, remote sensing and ground mobile mapping.**

IMPROVE SPAN IMU-ISA-100C ACCURACY

Take advantage of NovAtel CORRECT™ to receive your choice of accuracy and performance, from decimetre to RTK-level positioning. For more demanding applications, Inertial Explorer® post-processing software from our Waypoint® Products Group can be used to post-process SPAN IMU-ISA-100C data for the highest level of system accuracy.

BENEFITS

- + High performance IMU
- + Commercially exportable
- + Easy integration with NovAtel's SPAN capable GNSS+INS receivers
- + Ideal for aerial and hydrographic survey as well as industrial applications

FEATURES

- + Low noise fiber optic gyros and MEMS accelerometers
- + 200 Hz data rate
- + SPAN INS functionality

If you require more information about our SPAN products, visit www.novatel.com/span

IMU-ISA-100C

SPAN SYSTEM PERFORMANCE¹

Horizontal Position Accuracy (RMS)

| | |
|-----------------------|--------------|
| Single point L1/L2 | 1.2 m |
| NovAtel CORRECT™ | |
| » SBAS ² | 60 cm |
| » DGPS | 40 cm |
| » PPP ^{3, 4} | 4 cm |
| » RTK | 1 cm + 1 ppm |

Data Rate⁵

| | |
|------------------|--------|
| IMU measurements | 200 Hz |
| INS position | 200 Hz |
| INS velocity | 200 Hz |
| INS attitude | 200 Hz |

Time Accuracy⁶

20 ns RMS

Max Velocity⁷

515 m/s

IMU PERFORMANCE⁸

Gyroscope Performance

| | |
|----------------------------|---------------|
| Input range | ±495 deg/sec |
| Bias stability | ≥0.5 deg/hr |
| Scale factor repeatability | ≤100 ppm |
| Scale factor non-linearity | ≤100 ppm |
| Angular random walk | 0.012 deg/√hr |

Accelerometer Performance

| | |
|----------------------------|-------------|
| Range ⁹ | ±10 g |
| Bias repeatability | ≥1250 µg |
| Scale factor repeatability | ≤100 ppm |
| Scale factor non-linearity | ≤100 ppm |
| Velocity random walk | ≤100 µg/√hr |

PHYSICAL AND ELECTRICAL

Dimensions

180 x 150 x 137 mm

Weight

5.0 kg

Power

Power consumption

18 W (typical)

Input voltage +10 to +34 V

Connectors

Power SAL M12, 5 pin, male

Data SAL M12, 4 pin, female

Wheel sensor SAL M12, 8 pin, male

ENVIRONMENTAL

Temperature

Operating -40°C to +55°C

Storage -40°C to +85°C

Humidity MIL-STD-810G, Method 507.5

Random Vibe MIL-STD-810G, Method 514.6 (2.0 g)

MTBF >46,100 hrs

Environment IEC 60529 IP67

INCLUDED ACCESSORIES

- Power cable
- Communication cable
- Wheel sensor cable

OPTIONAL ACCESSORIES

- Inertial Explorer post-processing software

For the most recent details of this product:

www.novatel.com/products/span-gnss-inertial-systems/span-imus/

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada) or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia

61-400-883-601

Version 5 Specifications subject to change without notice.

©2016 NovAtel Inc. All rights reserved.

NovAtel, SPAN, Inertial Explorer and Waypoint are registered trademarks of NovAtel Inc.

OEM628, OEM638, FlexPak6, ProPak6 and NovAtel CORRECT are trademarks of NovAtel Inc.

D19539 May 2016

Printed in Canada.



Statements related to the export of products are based solely on NovAtel's experience in Canada, are not binding in any way and exportability may be different with respect to the export regulations in effect in another country. The responsibility for re-export of product from a Customer's facility is solely the responsibility of the Customer.

PERFORMANCE DURING GNSS OUTAGES^{1,10}

| Outage Duration | Positioning Mode | POSITION ERROR (M) | | VELOCITY ERROR (M/S) | | ATTITUDE ERROR (DEGREES) | | |
|-----------------|-------------------|--------------------|----------|----------------------|----------|--------------------------|-------|---------|
| | | Horizontal | Vertical | Horizontal | Vertical | Roll | Pitch | Heading |
| 0 s | RTK ¹¹ | 0.02 | 0.05 | 0.010 | 0.010 | 0.007 | 0.007 | 0.010 |
| | PPP | 0.06 | 0.15 | 0.010 | 0.010 | 0.007 | 0.007 | 0.010 |
| | SP | 1.20 | 0.60 | 0.010 | 0.010 | 0.007 | 0.007 | 0.010 |
| | PP ¹² | 0.01 | 0.02 | 0.010 | 0.010 | 0.003 | 0.003 | 0.004 |
| 10 s | RTK ¹¹ | 0.07 | 0.10 | 0.015 | 0.015 | 0.008 | 0.008 | 0.012 |
| | PPP | 0.11 | 0.20 | 0.015 | 0.015 | 0.008 | 0.008 | 0.012 |
| | SP | 1.25 | 0.65 | 0.015 | 0.015 | 0.008 | 0.008 | 0.012 |
| | PP ¹² | 0.01 | 0.02 | 0.010 | 0.010 | 0.003 | 0.003 | 0.004 |
| 60 s | RTK ¹¹ | 0.72 | 0.45 | 0.035 | 0.025 | 0.009 | 0.009 | 0.015 |
| | PPP | 0.76 | 0.55 | 0.035 | 0.025 | 0.009 | 0.009 | 0.015 |
| | SP | 1.90 | 1.00 | 0.035 | 0.025 | 0.009 | 0.009 | 0.015 |
| | PP ¹² | 0.04 | 0.02 | 0.030 | 0.010 | 0.003 | 0.003 | 0.004 |

1. Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

2. GPS-only.

3. Requires subscription to TerraStar data service. Subscriptions available from NovAtel.

4. An OEM628, OEM638, FlexPak6 or ProPak6 receiver is required.

5. 400 Hz data is an optional configuration. Contact NovAtel for details.

6. Time accuracy does not include biases due to RF or antenna delay.

7. Export licensing restricts operation to a maximum of 515 metres/second.

8. Supplied by IMU manufacturer.

9. GNSS receiver sustains tracking up to 4 g.

10. Ground Mobile Operating Environment.

11. 1 ppm should be added to all values to account for additional error due to baseline length.

12. Post-processing results using Inertial Explorer software.

